

选型数据表 Selection data sheet

DL-G 高压泵系列

DL-G High pressure pump series

型号 Model	流量 Capacity (m ³ /h)	级数 series	扬程 Head (m)	转速 Speed (r/min)	轴功率 Shaft power (kw)	必需汽 蚀余量 (NPSH) r(m)	泵体材质 Pump material	图纸批 准号 Drawing approval No.
DL-G8	8/9.6	2	80/115	2900/3500	4.6/7.9	2.1	HT200/QT450/ ZG07Cr19Ni10/ ZG03Cr19Ni11Mo2/ ZG03Cr22Ni6Mo3N	产品认可 product certificate
	8/9.6	3	120/172	2900/3500	6.9/11.8	2.1		
	8/9.6	4	160/230	2900/3500	9.2/15.8	2.1		
	8/9.6	5	200/288	2900/3500	11.5/19.8	2.1		
	8/9.6	6	240/345	2900/3500	13.8/23.8	2.1		
	8/9.6	7	280/403	2900/3500	16.1/27.7	2.1		
	8/9.6	8	320/460	2900/3500	18.4/31.8	2.1		
	8/9.6	9	360/518	2900/3500	20.6/35.6	2.1		
	8/9.6	10	400/576	2900/3500	22.9/39.6	2.1		
	8/9.6	11	440/634	2900/3500	25.2/43.6	2.1		
	8/9.6	12	480/691	2900/3500	27.5/47.5	2.1		
	8/9.6	13	520/748	2900/3500	29.8/51.4	2.1		
	8/9.6	14	560/806	2900/3500	32.1/55.4	2.1		
	DL-G13	13/15.6	2	80/115	2900/3500	5.9/10.2		
13/15.6		3	120/172	2900/3500	8.9/15.2	2.2		
13/15.6		4	160/230	2900/3500	11.8/20.4	2.2		
13/15.6		5	200/288	2900/3500	14.8/25.5	2.2		
13/15.6		6	240/345	2900/3500	17.7/30.6	2.2		
13/15.6		7	280/403	2900/3500	20.7/35.7	2.2		
13/15.6		8	320/460	2900/3500	23.6/40.7	2.2		
13/15.6		9	360/518	2900/3500	26.6/45.9	2.2		
13/15.6		10	400/576	2900/3500	29.5/51.0	2.2		
13/15.6		11	440/634	2900/3500	32.5/56.1	2.2		
13/15.6		12	480/691	2900/3500	35.4/61.2	2.2		
13/15.6		13	520/748	2900/3500	38.4/66.2	2.2		
13/15.6		14	560/806	2900/3500	41.3/71.4	2.2		
DL-G25		25m ³ /h	2	100/130	2900/3500	10.86/14.12	3.3	HT200/QT450/ ZG07Cr19Ni10/ ZG03Cr19Ni11Mo2/ ZG03Cr22Ni6Mo3N
	25m ³ /h	3	150/195	2900/3500	16.30/21.19	3.3		
	25m ³ /h	4	200/260	2900/3500	21.73/28.25	3.3		
	25m ³ /h	5	250/325	2900/3500	27.17/35.32	3.3		
	25m ³ /h	6	300/390	2900/3500	32.62/42.38	3.3		
	25m ³ /h	7	350/455	2900/3500	38.03/49.44	3.3		
	25m ³ /h	8	400/520	2900/3500	43.47/56.51	3.3		
	25m ³ /h	9	450/585	2900/3500	48.9/63.57	3.3		
	25m ³ /h	10	500/650	2900/3500	54.34/70.64	3.3		
	25m ³ /h	11	550/715	2900/3500	59.77/77.70	3.3		
	25m ³ /h	12	600/780	2900/3500	65.20/84.77	3.3		
	25m ³ /h	13	650/845	2900/3500	70.64/91.83	3.3		
	25m ³ /h	14	700/910	2900/3500	76.07/98.89	3.3		

DL-G30	30m ³ /h	2	100/130	2900/3500	12.81/16.69	3.5	HT200/QT450/ ZG07Cr19Ni10/ ZG03Cr19Ni11Mo2/ ZG03Cr22Ni6Mo3N	产品认可 product certific ate
	30m ³ /h	3	150/195	2900/3500	19.26/25.04	3.5		
	30m ³ /h	4	200/260	2900/3500	25.68/33.38	3.5		
	30m ³ /h	5	250/325	2900/3500	32.10/41.73	3.5		
DL-G30	30m ³ /h	6	300/390	2900/3500	38.52/50.08	3.5		
	30m ³ /h	7	350/455	2900/3500	44.94/58.42	3.5		
	30m ³ /h	8	400/520	2900/3500	51.36/66.77	3.5		
	30m ³ /h	9	450/585	2900/3500	57.78/75.12	3.5		
	30m ³ /h	10	500/650	2900/3500	64.20/83.46	3.5		
	30m ³ /h	11	550/715	2900/3500	70.62/91.81	3.5		
	30m ³ /h	12	600/780	2900/3500	77.04/100.16	3.5		
	30m ³ /h	13	650/845	2900/3500	83.46/108.50	3.5		
DL-G36	36m ³ /h	2	100/130	2900/3500	15.29/19.87	3.7		
	36m ³ /h	3	150/195	2900/3500	22.93/29.81	3.7		
	36m ³ /h	4	200/260	2900/3500	30.58/39.75	3.7		
	36m ³ /h	5	250/325	2900/3500	38.22/49.69	3.7		
	36m ³ /h	6	300/390	2900/3500	45.87/59.63	3.7		
	36m ³ /h	7	350/455	2900/3500	53.52/69.57	3.7		
	36m ³ /h	8	400/520	2900/3500	61.16/79.51	3.7		
	36m ³ /h	9	450/585	2900/3500	68.81/89.45	3.7		
	36m ³ /h	10	500/650	2900/3500	76.45/99.39	3.7		
	36m ³ /h	11	550/715	2900/3500	84.10/109.33	3.7		
	36m ³ /h	12	600/780	2900/3500	91.74/119.27	3.7		
	36m ³ /h	13	650/845	2900/3500	99.39/129.21	3.7		
DL-G42	42m ³ /h	2	100/130	2900/3500	17.70/23.01	3.9		
	42m ³ /h	3	150/195	2900/3500	26.55/34.52	3.9		
	42m ³ /h	4	200/260	2900/3500	35.41/46.03	3.9		
	42m ³ /h	5	250/325	2900/3500	44.26/57.54	3.9		
	42m ³ /h	6	300/390	2900/3500	53.11/69.04	3.9		
	42m ³ /h	7	350/455	2900/3500	61.96/80.55	3.9		
	42m ³ /h	8	400/520	2900/3500	70.82/92.06	3.9		
	42m ³ /h	9	450/585	2900/3500	79.67/103.57	3.9		
	42m ³ /h	10	500/650	2900/3500	94.84/123.30	3.9		
	42m ³ /h	11	550/715	2900/3500	97.37/126.59	3.9		
	42m ³ /h	12	600/780	2900/3500	106.23/138.09	3.9		
	DL-G50	50m ³ /h	2	100/130	2900/3500	20.76/26.99	3.9	
50m ³ /h		3	150/195	2900/3500	31.14/40.48	3.9		
50m ³ /h		4	200/260	2900/3500	41.52/53.98	3.9		
50m ³ /h		5	250/325	2900/3500	51.90/67.47	3.9		
50m ³ /h		6	300/390	2900/3500	62.28/80.97	3.9		
50m ³ /h		7	350/455	2900/3500	72.67/94.47	3.9		
50m ³ /h		8	400/520	2900/3500	83.05/107.96	3.9		
50m ³ /h		9	450/585	2900/3500	93.43/121.46	3.9		
50m ³ /h		10	500/650	2900/3500	103.81/134.95	3.9		
50m ³ /h		11	550/715	2900/3500	114.19/148.45	3.9		
50m ³ /h		12	600/780	2900/3500	124.57/161.95	3.9		